INST-SFP-BIDI-10K-AB-1/ INST-SFP-BIDI-10K-BA-1

iNS SFP Bi-Directional Single Mode Fibre Optic Transceivers

Features

- 'AB-1: 1550nmFP transmitter/1310nm receiver
- 'BA-1: 1310nmFP transmitter/1550 receiver
- Operating data rates up to 1.25Gbps
- 10km reach for 9/125µm Single Mode Fibre
- Single 3.3V power supply and TTL Logic Interface
- Low power dissipation
- Hot-pluggable SFP footprint
- BIDI LC/UPC type pluggable optical interface
- Class 1 FDA and IEC60825-1 laser safety compliant
- Built in digital diagnostic functions, including optical power monitoring
- RoHS compliant and lead-free
- Compliant with SFP MSA
- Compliant with SFF-8472
- Compliant with IEEE 802.3z

Description

INST-SFP-BiBi-10K-AB-1/INST-SFP-BiBi-10K-BA-1 are fibre optic transceivers for use with single mode fibre optic cable and operate at a nominal wavelength of 850nm.This dongle is locked and pre-configured for use with Kentec DNP-R-2F/FC-K Passive Dual Port Optic Fibre/RS485 Medium Converter.

Transceivers are hot-pluggable making them quick & easy to replace and also swap between alternate fibre optic modes. Maximum range will be dependent upon the fibre optic cable used 62.5/125µm range of 550m, 50/125µm can extend the range up to 1km.

The transmitter section uses a Vertical Cavity Surface Emitted Laser and is Class 1 laser compliant according to International Safety Standard IEC60825.

The receiver section uses an Integrated Gas detector pre-amplifier (IDP) mounted in an optical header and a limiting post-amplifier IC. 'AB-1/'BA-1 are designed to be compliant with SFF-8472 MSA.

Built in digital diagnostic functions allow monitoring of the transceiver by the DNP-R-2F/FC-K converter module and subsequently the IVIEW software tool. This allows performance monitoring along with early warning of a potential issue to enable preventative maintenance.

iNS Product	
INST-SFP-BiDi-10K-AB-1	iNS SFP Bi-directional single mode fibre optic transceiver [1550nm TX/1310nm RX]
INST-SFP-BiDi-10K-BA-1	iNS SFP Bi-directional single mode fibre optic transceiver [1310nm RX/ 1550nm TX]

Specifications

General Product Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Bit Rate	BR			1.25	Gb/s
Max. Supported Link Length	L(max)			10	km

Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Unit
Storage Temperature	$T_{(case)}$	-40	+85	°C
Supply Voltage	Vcc	-0.5	4	V
Storage Ambient Humidity	H_A	5	95	%

Optical Characteristics					
Parameter	Symbol	Min.	Typ	Max.	Unit
9/125µm Diameter SMF	L		10		km
Power Supply Voltage	Vcc	3.13	3.3	3.47	V
Power Supply Current	Icc			280	mA
Data Rate - GBE					Mbps (Tx/Rx Rate)
Transmitter					
Centre Wavelength	λc	1260	1310	1360	nm
		1530	1550	1570	
Spectral Width (RMS)	σ			3.5	Nm(FP Laser Tx:1310nm)
Average Output Power	P out	-9		-3	dBm
Extinction Ratio	ER	9			dB
Side Mode Suppression Ratio	SMSR	30			dB(DFB Laser Tx:1550nm)
Total Jitter	T_J			0.1	UI
Output Optical Eye	IEEE802.3z Compliant (Class 1 laser safety)				
Spectrum Bandwidth (-20dB)	σ				
P out@Tx Disable Asserted	P_{off}			-45	dBm
Receiver					
Optical Input Wavelength	$λ_{IN}$	1550	1550	1600	nm
		1290	1310	1330	
Receiver Sensitivity	P_{IN}			-23	dBm
Receiver Overload	P_{SAT}	-3			dBm
LOS De-assert	P_D			-22	dB
LOS Assert	P_A	-45			dBm
LOS Hysteresis	P_D - PA	0.5		6	dB

For further information visit www.kentec.co.uk
Kentec Electronics Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Kentec Electronics Ltd. to be a complete and up-to-date description.